



Stabilizer Solutions, Inc.
33 S. 28th St.
Phoenix, AZ 85034
800-336-2468 (Fax) 602-225-5902
Website: stabilizersolutions.com
E-Mail: info@stabilizersolutions.com

PART 1 - STALOK® BUNKER LINER

- A. StaLok® Bunker liner is a solely owned proprietary and patented process.
- B. Blending procedures are performed only by licensed StaLok® blender and can only be sold through licensed StaLok® Dealers.
- C. StaLok® Dealers and Stabilizer Dealers may not necessarily be the same.
- D. StaLok® Bunker Seal is a flexible and stable compound for protection of bunkers from sub-grade invasion into bunker sand and sand integrating with the sub-grade.

PART 2 – EXECUTION

STALOK® BUNKER LINER

- A. Sub-grade
 1. Compacted sub-grade is required.
 2. Existing sub-grade, which will not readily compact as required, shall be replaced with satisfactory materials.
 3. Areas being graded or compacted shall be kept, shaped, and drained.
- B. StaLok® Bunker Liner
 1. Contractor will spread StaLok® evenly 2-inches throughout bunker.
 2. Contractor shall compact once the surface is level and at correct thickness – compacted 2-inches.
 - a. Compaction equipment will be comprised of 1000-lb self propelled roller, 900-lb water fill roller, upright Rammer – 10”-13” foot, Forward Plate Compactors 24” X 20” plate (4000-lb Centrifuged force), Reversible Plate Compactor, Vibratory plate compactor, hand held pneumatic side wall compactor, close quarter’s Plate Compactor, 8” hand tamps or equal.
 3. There shall not be loose material present on final surface.
 4. Once surface is properly compacted contractor can immediately return sand back to bunker.

PART 3 – MAINTENANCE, REPAIRS, AND WARRANTY

- A. Repairs
 1. Excavate damaged area to the depth of the bunker liner, square up the excavated sides and add StaLok® Bunker Liner as needed, compact, compact, compact.
 2. Return sand to the repaired areas.
- B. Warranty
 1. Manufacturer warrants the material supplied under our contract to be in accordance with the project drawings and specifications. Contractor warrants installation of product for the time of one year.
 2. Contractor shall provide maintenance and repairs as required for a period of 60-days.